

Item no.

Adapter type

Frequency Range
 Impedance (Nom.)
 Power Rating

Product photo



Transfer Impedance (CoMeT)

 Screening Attenuation(CoMeT)

Return Loss	Better than	Typical
0.3 - 500 MHz	-28 dB	-31,2 dB
500 - 860 MHz	-21 dB	-23,9 dB
860 - 1000 MHz	-19 dB	-22,0 dB
1000 - 1750 MHz	-13 dB	-16,3 dB
1750 - 2150 MHz	-12 dB	-15,3 dB
2150 - 3000 MHz	-12 dB	-14,9 dB

Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-	-
500 - 860 MHz	-	-
860 - 1000 MHz	-	-
1000 - 1750 MHz	-	-
1750 - 2150 MHz	-	-
2150 - 3000 MHz	-	-

Temperature
 Installing
 Operating
 Storing

Intermodulation
 3rd Order (@2x100mW)

Inner Conductor Resistance
 (@ 1 A DC)

Sealing Test
 (IEC IP-code)

Insulation Resistance
 (@ 500 VDC)

O-rings

Dielectric Strength
 AC Test Voltage

Base Material
 Body Parts
 Inner Conductor

Max. Tensile Strength
 Overall

Plating
 Body Parts
 Inner Conductor

Torsional Strength
 (Connector / Cable)

Insulators

Test performed by
 Date

Remarks * Signal level 1/2W@75 ohm equals +134dBμV
 ** Printed Circuit Board made of CEM3.

*All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
 Further technical specifications and installation instructions can be obtained on request.*